

HM2 (HM201 Handset)



Hotel/hospitality features



DECT



HD audio



Anti-bacterial housing

Basics

- Product information
 - DECT handset | charging cradle | PN 00007007
 - Colour: gunmetal black
- Availability:
 - **Bundle HM201** (HM2 DECT handset | HM201 Base station), EU & UK, PN **00007006**
- Placement: indoor, desktop, nightstand
- Sturdy, solid construction
- Ultra small footprint and compact design
- Anti-bacterial housing

Dimensions and weight

- Dimensions (H x W x D, approx.)
 - Handset: 180 mm x 50 mm x 15 mm
 - Charging cradle: 32 mm x 50 mm x 63 mm
 - Handset (on the charging cradle): 190 mm x 50 mm x 63 mm
- Weight (approx.)
 - Handset: 147 g
 - Charging cradle: 215 g
 - Handset (on the charging cradle): 357 g

Display

- TFT liquid crystal display (LCD), true colour, extra slim, backlit
- Size (diagonal): 2.8" (71 mm)

Keypad and function keys

- 24 hard keys in total
- 12 keys (standard ITU telephone keypad), backlit
- 3 context-sensitive function keys
- 4 dedicated audio keys
 - Mute, Speakerphone, Volume +, Volume -
- 5 dedicated function keys
 - Onhook, Offhook, Message, front desk, Emergency

Audio devices and features

- Microphone
 - Hearing aid compatible (HAC)
- Handset earpiece
 - Speakerphone mode (via dedicated function key)

Interfaces and connections

- Power options
 - Handset: Battery lithium-ion 3.7 V, 1,000 mAh, preinstalled, removable, rechargeable, up to 7 h talk time, up to 120 h standby time, up to 11 h charging time
 - Charging cradle: Power adapter¹ 100 - 240 V (AC), 50 - 60 Hz, 150 mA | 6 V, 450 mA, 2.7 W
- Wired interfaces
 - Charging cradle: RJ-11 socket
- Wireless interfaces
 - DECT

DECT technology and features

- Standard: DECT
 - Authentication/encryption of base and handset
 - Wideband audio
- Frequency band
 - EU & UK: 1,881.792 - 1,897.344 MHz

User interfaces and setup

- Comfortable and intuitive menu structure
- Real time clock, room number, and guest name programming available
- Low battery indication
- Remote maintenance

Call features

- Quick call answer (by simple pick-up from the base/charger)
- Speed dialling: up to 10 (scrolling list on the display)
- Mute microphone (via dedicated function key)

Environmental conditions

- Operating ambient temperature: 0 °C - 40 °C

¹ Included in bundle HM201

- Humidity (non-condensing): 65 ± 20 %

Snom accessories and compatible devices

- Power adapter:¹ Charging cradle PSU
 - EU: PN 00004697
 - UK: PN 00004698
 - AU: PN 00004699
- Battery¹ HM2 (PN 00004627)

Series overview



HM201



HD100



HD101



HD1



HD350W



HD351W



HD3

Disclaimer

Further information: [Snom website](#) | [Snom Service Hub](#) | [Type approval](#) | [Warranty information](#)

Snom, the names of Snom products, and Snom logos are trademarks owned by Snom Technology GmbH. All product specifications are subject to change without notification. Snom Technology GmbH reserves the right to revise and change this document at any time, without being obliged to announce such revisions or changes beforehand or after the fact. Although due care has been taken in the compilation and presentation of the information in this document, the data upon which it is based may have changed in the meantime. Snom therefore disclaims all warranties and liability for the accurateness, completeness, and currentness of the information published, except in the case of intention or gross negligence on the part of Snom or where liability arises due to binding legal provisions.